

HPC cluster Initiation

www.southgreen.fr

<https://southgreenplatform.github.io/trainings>





Julie ORJUELA-BOUNOL¹, IE
Bioinformaticienne
25%



Ndomassi TANDO, IE
Administrateur systeme
100%
Animateur plateau



Christine TRANCHANT-DUBREUIL, IE
Bioinformaticienne
20%

Aurore COMTE, IE
Bioinformaticienne
20%

Alexis DEREPPER², IE
Bioinformaticien
20%



Valérie NOEL, TCS
Bioinformaticienne
25%



Bruno GRANOUILAC³, IE
Systèmes d'information
20%

Provisioning of
softwares and HPC
ressources

Analysis software
and IS development

Plateau bioinformatique

Help and support
to IRD teams

Training to north
and South

- Site <https://bioinfo.ird.fr>
 - Accounts
 - Softwares installation
 - Projects
 - Installed softwares
- Incidents: contact bioinfo@ird.fr




ARCHITECTURE

- A logical unit composed of several servers
- A powerful unique machine
- Allow to obtain high computing performance
- A bigger capacity storage
- More reliable
- A better resources availability

- A logical unit composed of several servers
- A powerful unique machine
- Allow to obtain high computing performance
- A bigger capacity storage
- More reliable
- A better resources availability



- A logical unit composed of several servers
- A powerful unique machine
- Allow to obtain high computing performance
- A bigger capacity storage
- More reliable
- A better resources availability





- **Master Node**
Handle resources and jobs priorities
- **Computing nodes**
Resources (CPU or RAM memory)

COMPUTING



- **Master Node**
Handle resources and jobs priorities
- **Computing nodes**
Resources (CPU or RAM memory)

STORAGE



- **NAS Server(s)**
Storage

- **1 Master Node**



bioinfo-master.ird.fr

Role :

- Launch and prioritize jobs on computing nodes
- Accessible from the Internet
- Connection :

```
ssh login@bioinfo-master.ird.fr
```

- **1 Master Node**




bioinfo-master.ird.fr

Role :

- Launch and prioritize jobs on computing nodes
- Accessible from the Internet
- Connection :

```
ssh login@bioinfo-master.ird.fr
```

- **25 computing nodes**



nodeX
X : 1..25

Role :

- Used by the master to execute jobs
- Not accessible from the Internet
- node0 to node25
- Connection from master

```
ssh nodeX
```

● 1 Master Node




bioinfo-master.ird.fr

Role :

- Launch and prioritize jobs on computing nodes
- Accessible from the Internet
- Connection :

```
ssh login@bioinfo-master.ird.fr
```

● 25 computing nodes



nodeX
X : 1..25

Role :

- Used by the master to execute jobs
- Not accessible from the Internet
- node0 to node25
- Connection from master

```
ssh nodeX
```



Interactif node (node6)

- Accessible from the Internet: bioinfo-inter.ird.fr
- Connection :

```
ssh login@bioinfo-inter.ird.fr
```



Practice

Step 1: Connection, qhost

1

Go to the [Practice 1](#) of *github*

Connection
to
bioinfo-mas
ter.ird.fr
and
resources
reservation




Step 1
qrsh/qlogin
or qsub

Queues	Use	RAM features of the nodes	Cores features of the nodes
bioinfo.q	Short Jobs < 3days	48 to 64 GB	12 to 20 cores
longjob.q	Long Jobs > 3 days	48 GB	12 cores
bigmem.q	Jobs with extra memory needs	96 GB	12 cores
highmem.q	Jobs with big memory needs	144 GB	12 cores

How do I choose the queue?

Queue choice




NO


<3d

YES


How do I choose the queue?




How do I choose the queue?




How do I choose the queue?




How do I choose the queue?



How do I choose the queue?



How do I choose the queue?



- **1 Master node**




bioinfo-master.ird.fr

Role :

- Launch and prioritize jobs on computing nodes
- Accessible from the Internet

- **25 computing nodes**



Role :

- Used by the master to execute jobs
- Not accessible from the Internet

- **3 NAS servers**



Bioinfo-nas.ird.fr
(nas)


Bioinfo-nas2.ird.fr
(nas2)

Bioinfo-nas3.ird.fr
(nas3)


Role :

- Store users data
- Accessible from the Internet
- To transfer data : *via filezilla or scp*

cluster i-Trop disk partitions




bioinfo-nas.ird.fr



bioinfo-nas2.ird.fr




bioinfo-nas3.ird.fr




bioinfo-master.ird.fr

Virtual links to the other servers partitions



25 nodes



Connection
to
bioinfo-mas
ter.ird.fr
and
resources
reservation



Creation of
the analyses
folder in the
/scratch of
the node

Step 1

Step 2
mkdir



Practice


Step 2:qrsh, partition

2

Go to the [Practice2](#) of the github




PC/MAC




**direct transfer
via filezilla
forbidden**

**bioinfo-master.ird.fr
91.203.34.148**

Data transfer on i-Trop cluster





Copy your data from your PC/MAC to the nas serve if they are not on the cluster



Practice

Step 3: filezilla

3

Go to the [Practice3](#) of the github

- Copy between 2 remote servers :

```
scp -r source destination
```


- Syntax if the source is remote :

```
scp -r server_name:/path/file_to_copy local_folder
```

- Syntax if the destination is remote :

```
scp -r /path/file_to_copy server_name:/path/remote_folder
```

Ex: `scp -r nas:/home/tando/folder/ /scratch/tando/`





Practice

Step 4: scp to nodes


4

Go to the [Practice4](#) of the github

- Allow to choose the version of software you want to use
- 2 types of softwares :
 - bioinfo : includes all the bioinformatics softwares (example BEAST)
 - system : includes all the system softwares(example JAVA)
- Overcome the environment variables

- 5 types of commands :
 - See the available modules :
`module avail`
 - Obtain infos on a particular module:
`module whatis + module name`
 - Load a module :
`module load + modulename`
 - List the loaded module :
`module list`
 - Unload a module :
`module unload + modulename`
 - Unload all the modules :
`Module purge`

Analyses steps of the cluster



Step 1

Step 2

Step 3

Step 4

Load
softwares
with
modules
environment

Step 5
module




Practice

Step 5: module environment

5

Go to the [Practice5](#) of the github

Analyses steps of the cluster



- Load the software version to launch
- Launch the data analysis

```
$~ command <options> <arguments>
```

With *command*: the command to launch

- Execute a bash command via qsub
- Launch the command from a node
- We use:

```
$~ qsub -b y "command"
```

With *command*: the command to launch

Options	Description	Exemple
<code>qsub -N <name></code>	Give a name to the job	<code>qsub -N tando_blast</code>
<code>qsub -q <queue></code>	Choose a particular queue	<code>qsub -q highmem.q</code>
<code>qsub -l hostname=<nodeX></code>	Choose a particular node	<code>qsub -l hostname=node10</code>
<code>qsub -pe <ompi X></code>	Launch a several cores jobs	<code>qsub -pe ompi 4</code>
<code>qsub -M <emailaddress></code>	Send an email	<code>qsub -M ndomassi.tando@ird.fr</code>
<code>qsub -m <eab></code>	Send an email when: e: end of the job a: abort b: begin of the job	<code>qsub -m be</code>
<code>qsub -cwd</code>	Launch a job from the current working directory	<code>qsub -cwd script.sh</code>



Practice

Step6: launch the analysis

6

Go to the [Practice6](#) of the github

- Copy between 2 remote servers :

```
scp source destination
```


- Syntax if the source is remote :

```
scp server_name:/path/file_to_copy local_folder
```

- Syntax if the destination is remote :

```
scp /path/file_to_copy server_name:/path/remote_folder
```

Analyses steps of the cluster





Practice

Step 7: Retrieve the results


7

Go to the [Practice7](#) of the github

- Scratch= temporary spaces
- Verify that the copy is OK before
- Use rm command

```
cd /scratch  
rm -rf nom_rep
```

Analyses steps of the cluster





Practice

Step8: Data deletion

8

Go to the [Practice8](#) of the github

Scripts to visualize/delete données temporary data

- Scripts location: /opt/scripts/scratch-scripts
- Visualize data on scratches: scratch_use.sh

```
sh /opt/scripts/scratch-scripts/scratch_use.sh
```

- Delete data on scratches: clean_scratch.sh

```
sh /opt/scripts/scratch-scripts/clean_scratch.sh
```

BONUS

LAUNCH A JOB

- Scheduler choose resources automatically
- Use up to 24 cores at the same time
- Possibility to configure this choice
- Jobs launch in background
 - possibility to turn off your PC/MAC
 - automatic results retrieving

- Execute a script via sge
- Use:

```
$~ qsub script.sh
```

with script.sh : the name of the script

Options	Description	Exemple
<code>qsub -N <name></code>	Give a name to the job	<code>qsub -N tando_blast</code>
<code>qsub -q <queue></code>	Choose a particular queue	<code>qsub -q highmem.q</code>
<code>qsub -l hostname=<nodeX></code>	Choose a particular node	<code>qsub -l hostname=node10</code>
<code>qsub -pe <ompi X></code>	Launch a several cores jobs	<code>qsub -pe ompi 4</code>
<code>qsub -M <emailaddress></code>	Send an email	<code>qsub -M ndomassi.tando@ird.fr</code>
<code>qsub -m <eab></code>	Send an email when: e: end of the job a: abort b: begin of the job	<code>qsub -m be</code>
<code>qsub -cwd</code>	Launch a job from the current working directory	<code>qsub -cwd script.sh</code>

First part of the script (in green): sge execution options with the key word # $\$$

```
#!/bin/sh

##### SGE CONFIGURATION #####
# write errors in standard outputfile
# $\$$  -j y

# Shell we want to use
# $\$$  -S /bin/bash

# Email to follow the job
# $\$$  -M prenom.nom@ird.fr      ##### Mettre son adresse mail

# Type of messages by mail
# - (b) beginning message
# - (e)end message
# - (a) abort message
# $\$$  -m bea

# Queue to use
# $\$$  -q bioinfo.q

# Name of the job
# $\$$  -N name_to_choose
#####
```


In the 2nd part of the script: the command to execute

```
path_to_dir="/data/projects/folder_to_choose";
path_to_tmp="/scratch/name_folder_to_choose-$JOB_ID"

##### Create the temporary folder on the node and load the blast module
module load bioinfo/blastn/2.4.0+
mkdir $path_to_tmp
scp -rp nas2:$path_to_dir/* $path_to_tmp # choose nas for /home, /data2 and /teams or nas2 for /data or nas3 for /data3
echo "tranfert from master -> noeud";
cd $path_to_tmp

##### Program execution
cmd="blastn -db All-EST-coffea.fasta -query sequence-NMT.fasta -num_threads $NSLOTS -out blastn1-$JOB_ID.out";
echo "executed command : $cmd";
$cmd;

##### Data transfer from node to nas
scp -rp $path_to_tmp/ nas:$path_to_dir/
echo "Transfert from node -> master";

#### Deletion of the tmp folder
rm -rf $path_to_tmp
echo "Deletion on the node";
```



Practice

Launch a script with sge

9

Go to the [Practice9](#) of the github

If you use i-Trop Bioinformatics resources.

Thank you for citing with:

“The authors acknowledge the IRD itrop HPC (South Green Platform) at IRD montpellier
for providing HPC resources that have contributed to the research results reported within this paper.

URL: <https://bioinfo.ird.fr/>- <http://www.southgreen.fr>”

- Include a budget for bioinformatics resources in your answer to projects funding
- A need in hard drives, renewal machines etc...
- Available quotations
- Contact bioinfo@ird.fr : help, needs definition, quotations...

Thank you for your attention !



Le matériel pédagogique utilisé pour ces enseignements est mis à disposition selon les termes de la licence Creative Commons Attribution - Pas d'Utilisation Commerciale - Partage dans les Mêmes Conditions (BY-NC-SA) 4.0 International:

<http://creativecommons.org/licenses/by-nc-sa/4.0/>